

TIP SHEET

Sales 7ips About Competitors & Their Products

COMPANY	ADVANCE LIFTS
MODEL	P-2536* (LS2-36)

DATE ISSUED 08/19/98

TIP SHEET NO. 28

DATE REVISED 12/20/01

Advance Lifts offers two grades of lift; a standard and a deluxe duty. It is likely, in most competitive situations, the standard will be quoted. The deluxe model, with its better features, has a list price as much as 23% more than the standard model. Southworth manufactures only one grade of lift. It is designed and manufactured to be the best money can buy and it is packed with the features that set it a class above.

<u>Feature</u>	<u>Advance</u>	<u>Southworth</u>	Comment
Cylinder vent	To atmosphere	To reservoir	Normal cylinder weepage is directed to reservoir, not to the floor
Wear indicating rollers	No	Yes	Maintenance made easy
Comfort edge	No	Yes	Platform fitted with full perimeter "user friendly" soft molded edge
Roller retainers	No	Yes	Retainers prevent the platform from "tipping up" under impact from loads bouncing onto the hinged end of the platform
Down speed	Fixed	Adjustable	Permits adjusting the lift speed exactly as needed by the application
Operating pressure	Up to 3200 psi	Up to 1900 psi	Lower operating pressures reduce the possibility of leakage and extends seal life
Hydraulic cylinder	(1) 2-1/2" bore	(1) 3 ½" bore	The Southworth cylinders operate at over 1,000 psi less and have a brass scraper on the rod which helps prolong seal life
Pivot pins	Pressed/welded	Full width	All Southworth roller and axle pins span the full width-promotes straighter tracking of the legs throughout the full travel range of the lift
Scissors legs	Welded assembly	Profile cut	Southworth offers ideal one-piece design over manufacturing short cuts . Full profile puts maximum width at the main axle pin - where it is needed and with no welded blocks on the legs
Capacity - end loading (based on maximum, 4' x 6' platform)	858 lb. rating	1,000 lb. rating	More capacity to handle the repeated impact of axle loads bouncing across the ends of the platform

*formerly model AL2-36